

## **Claim amendments**

### **Listing of Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently amended) A lighting device according to an embodiment of the present invention comprising:

a first socket assembly having a first socket which is made of a soft and elastic bar shape conductor, on which a plurality of lamp inserting holes are formed along a longitudinal direction, and a first socket holder in which the socket is received and which is made of an insulator having higher rigidity than the socket wherein the first socket is made of a conductive rubber, which is molded by silicone rubber mixed with carbon black;

a second socket assembly having a second socket which is made of a soft and elastic bar shape conductor and on which a plurality of lamp inserting holes are formed along a longitudinal direction, and a second socket holder in which the socket is received and which is made of an insulator having higher rigidity than the socket and is placed to face the first socket assembly;

a plurality of fluorescent lamps having a glass lamp vessel each one end of which is inserted in one of the plurality of lamp inserting holes of the first socket in the first socket assembly, and each other end of which is inserted in one of the plurality of lamp inserting holes of the second socket in the second socket assembly wherein the plurality of fluorescent lamps is a dielectric barrier type discharge lamp having a glass lamp vessel, on both end of which an external electrode is formed; and

a high frequency power source which supplies a high frequency voltage between the first socket in the first socket assembly and the second socket in the second socket assembly.

2-3. (Canceled)

4. (Currently amended) A lighting device according to claim 3 1, wherein the first socket is made of a conductive rubber, which is molded by silicone rubber mixed with carbon black of 30 to 40 wt. % and silica of 1 to 10 wt. %.

5. (Original) A lighting device according to claim 4, wherein the external electrode of the dielectric barrier type discharge lamp has an outer diameter somewhat larger than the lamp inserting hole of the first or second socket, and has a length with which an end of the external electrode protrudes from the other side of the first or second socket when the external electrode is inserted in the lamp inserting hole.

6. (Previously presented) A lighting device according to claim 1, wherein the first or second socket is provided with a harness connection portion, which is a concave portion formed at an end of the socket, and a metal fitting for screwing the harness terminal connected with said high frequency power source is fitted in the concave portion of the harness connection portion.

7. (Original) A lighting device according to claim 6, wherein the harness-connecting portion is provided with a metal nut for screwing the harness terminal, which is fixed by burning on the bar shape conductor forming the first or second socket.

8. (Original) A lighting device according to claim 7, wherein the metal nut has a peripheral shape of a polygon or a circle with projections.

9. (Original) A lighting device according to claim 8, wherein a screw boss is fixed on one end of the first or second socket holder and a insertion hole for inserting the screw boss is formed on one face of the first or the second socket where the harness connecting portion is provided,

wherein a through hole, which communicates with the inserting hole, is provided on the other face of the first or second socket holder, and

wherein the first or second socket is fixed on the first or second socket holder respectively, by coupling the screw inserted in the through hole with the screw boss.

10. (Currently amended) A lighting device according to claim 1, wherein the first socket is provided with ~~the~~ a harness-connecting portion on its one end portion, and the second socket is provided with ~~the~~ a harness-connecting portion on its end portion, which is located at an opposite side of the end portion of the first socket, so that each circuit for supplying a high

frequency voltage to each of the discharge lamps from the high frequency power source has a nearly equal circuit length.

11. (Currently amended) A lighting device according to claim 2 1, wherein a plurality of fixing protrusions are provided along a longitudinal direction on the first or second socket holder, and a plurality of fixing holes having an opening area somewhat smaller than the cross section of the fixing protrusions are provided along a longitudinal direction on the first or second socket so that the first or second socket is received in the first or second socket holder by pressing the plurality of fixing protrusions into the plurality of fixing holes.

12. (Original) A lighting device according to claim 10, wherein the first or second socket holder is made of a flame resistant insulator, and is constructed to cover the side face of the first or second socket except for the face where the plurality of lamp insertion holes are open.

13. (Currently amended) A socket assembly for a fluorescent lamp comprising:  
a first socket assembly including a first socket which is composed of a soft and elastic bar shape conductor which is provided with a plurality of lamp inserting holes along a longitudinal direction, and a first socket holder in which the socket is received and which is made of an insulator having higher rigidity than the socket wherein the first socket is made of a conductive rubber, which is molded by silicone rubber mixed with carbon black; and

a second socket assembly including a second socket which is made of a soft and

elastic bar shape conductor and which is provided with a plurality of lamp inserting holes along a longitudinal direction, and a second socket holder in which the socket is received, which is made of an insulator having higher rigidity than the socket, and which faces the first socket assembly with a space.

14. (Canceled)

15. (Currently amended) A socket assembly for a fluorescent lamp according to claim ~~14~~ 13, wherein the first socket is made of a conductive rubber, which is molded by silicone rubber mixed with carbon black of 30 to 40 wt. % and silica of 1 to 10 wt. %.

16. (Original) A socket assembly for a fluorescent lamp according to claim 15 wherein the first or second socket is provided with a harness-connecting portion, which is a concave portion formed at an end of the socket, and a metal fitting for screwing the harness terminal connected with the high frequency power source is fitted in the concave portion of the harness connecting portion.

17. (Currently amended) A socket assembly for a fluorescent lamp according to claim ~~15~~ 16, wherein the harness-connecting portion is provided with a metal nut for screwing the harness terminal, which is fixed by burning on the bar shape conductor forming the first or second socket.

18. (Original) A socket assembly for a fluorescent lamp according to claim 17, wherein the metal nut has a peripheral shape of a polygon or a circle with projections.

19. (Original) A socket assembly for a fluorescent lamp according to claim 18, wherein a screw boss is fixed on one end of the first or second socket holder and a insertion hole for inserting the screw boss is formed on one face of the first or the second socket where the harness connecting portion is provided,

wherein on the other face of the first or second socket holder, a through hole, which communicates with the inserting hole, is provided, and

wherein the first or second socket is fixed on the first or second socket holder respectively, by coupling the screw inserted in the through hole with the screw boss.

20. (Original) A socket assembly for a fluorescent lamp according to claim 13, wherein a plurality of fixing protrusions are provided along a longitudinal direction on the first or second socket holder, and a plurality of fixing holes having an opening area somewhat smaller than the cross section of the fixing protrusions are provided along a longitudinal direction on the first or second socket, so that the first or second socket is received in the first or second socket holder by pressing the plurality of fixing protrusions into the plurality of fixing holes.

21. (Original) A socket assembly for a fluorescent lamp according to claim 20, wherein the first or second socket holder is made of a flame resistant insulator, and is constructed to cover the side face of the first or second socket except for the face where the plurality of lamp insertion holes are open.

22. (Currently amended) A power supply unit for a fluorescent lamp comprising:  
a first socket assembly including a first socket which is made of a soft and elastic bar shape conductor which is provided with a plurality of lamp inserting holes along a longitudinal direction, and a first socket holder in which the socket is received and is made of an insulator having higher rigidity than the socket wherein the first socket is made of a conductive rubber, which is molded by silicone rubber mixed with carbon black;

a second socket assembly including a second socket which is made of a soft and elastic bar shape conductor which is provided with a plurality of lamp inserting holes along a longitudinal direction, and a second socket holder in which the socket is received, which is made of an insulator having higher rigidity than the socket, and which faces the first socket assembly with a space; and

a high frequency power source, which supplies a high frequency voltage between the first socket of the first socket assembly and the second socket of the second socket assembly.

23. (Canceled)

24. (Currently amended) A power supply unit for a fluorescent lamp according to claim ~~23~~ 22, wherein the first socket is composed of a conductive rubber, which is molded by silicone rubber mixed with carbon black of 30 to 40 wt. % and silica of 1 to 10 wt. %.

25. (Original) A power supply unit for a fluorescent lamp according to claim 22, wherein the first socket is provided with the harness-connecting portion on its one end portion, and the second socket is provided with the harness-connecting portion on its end portion, which is located at an opposite side of the end portion of the first socket, so that each circuit for supplying a high frequency voltage to each of the plurality discharge lamps of dielectric barrier type from the high frequency power source has a nearly equal circuit length.

26. (Canceled)

27. (Currently amended) A lighting device according to claim ~~2~~ 1, wherein the first or second socket is provided with a harness connection portion, which is a concave portion formed at an end of the socket, and a metal fitting for screwing the harness terminal connected with said high frequency power source is fitted in the concave portion of the harness connection portion.

28. (Previously presented) A lighting device according to claim 27, wherein the harness-connecting portion is provided with a metal nut for screwing the harness terminal, which is fixed by burning on the bar shape conductor forming the first or second socket.



29. (Previously presented) A lighting device according to claim 28, wherein the metal nut has a peripheral shape of a polygon or a circle with projections.

30. (Previously presented) A lighting device according to claim 29, wherein a screw boss is fixed on one end of the first or second socket holder and an insertion hole for inserting the screw boss is formed on one face of the first or the second socket where the harness connecting portion is provided,

wherein a through hole, which communicates with the inserting hole, is provided on the other face of the first or second socket holder, and

wherein the first or second socket is fixed on the first or second socket holder respectively, by coupling the screw inserted in the through hole with the screw boss.

31. (Currently amended) A lighting device according to claim 2 1, wherein the first socket is provided with the harness-connecting portion on its one end portion, and the second socket is provided with the harness-connecting portion on its end portion, which is located at an opposite side of the end portion of the first socket, so that each circuit for supplying a high frequency voltage to each of the discharge lamps from the high frequency power source has a nearly equal circuit length.

32. (Previously presented) A lighting device according to claim 31, wherein the first or second socket holder is made of a flame resistant insulator, and is constructed to cover the side face of the first or second socket except for the face where the plurality of lamp insertion holes are open.

33. (Previously presented) A lighting device according to claim 1, wherein the first socket is made of a conductive rubber, which is molded by silicone rubber mixed with carbon black.

34. (Previously presented) A lighting device according to claim 33, wherein the first socket is made of a conductive rubber, which is molded by silicone rubber mixed with carbon black of 30 to 40 wt. % and silica of 1 to 10 wt. %.